

CMYX

COLOR MARK SENSOR

Increase process throughput with high-speed, accurate and reliable color mark detection. The CMYX™ employs our field-proven, patented technology, combining a broad-spectrum light source, small spot size and fast response to achieve high-speed mark detection capable of detecting standard one-track PHARMA-CODE (0.5mm thin bar width) at 2000ft/min. The metal alloy case and glass lens provide robust construction expected in an industrial environment.

Whether you need to verify color mark presence or measure the position of the print-to-cut triangle, the CMYX provides the accuracy and precision for reliable process control.

The CMYX features a 2-digit display that provides an indication of signal strength making set-up and integration quick and easy. The versatile sensor provides user set-up parameters including light source intensity adjustment, detection threshold and gain selection making the CMYX useful in a wide range of applications.

The CMYX includes a discrete PNP/NPN output that is automatically set for PNP or NPN operation.

CMYX



EMX Industries, Inc.

4564 Johnston Parkway, Cleveland, Ohio 44128

P. 800 426 9912 F. 216 518 9884

Sales Inquiries: salesupport@emxinc.com **Technical Support:** technical@emxinc.com
www.emxinc.com



Applications

- Color verification
- Printing processes
- Registratin mark detection
- Print-to-cut control, folder gluer applications
- Pharma code
- Small part detection

Design & Features

- 0.4mm spot size
- 25uS response time
- Display range 00-99
- Broad spectrum white LED
- Adjustable gain
- Programmable discrete output
- Automatic and manual threshold adjustment
- Small size

Ordering Information



CMYX
Color Mark Sensor

Accessories



UVX-300B
Bracket



UVX-300C
Cable 5P, 5M, M12, F

Functions

NORMAL OPERATING MODE
CALIBRATION
THRESHOLD
LED INTENSITY
HYSTERESIS LEVEL
DISCRETE OUTPUT
SECURITY
TEACH MODE

Displays relative reflection intensity
 User sensitivity adjustment
 Set detection level
 Set LED, LO, MED, HI
 Set undetect level 1-9 steps below threshold
 Set normally open or normally closed
 Lock/unlock pushbutton controls
 Auto-set detection threshold

Specifications

White light source
Sensing distance
Spot size
Distance Variation Sensitivity
Response time
Switching Frequency
LED intensity
Relative intensity display range
Sensitivity
Signal level
Detection threshold
Digital Output
Output Function
Security
Power indicator
Detect indicator
Programming indicator
Data retention
Dimensions
Weight
Supply Voltage
Operating Current
Short Circuit Protection
Overload / Reverse Polarity Protection
Operating temperature
Storage temperature
Housing
Mechanical Protection

LED, min. 100,000 hrs.

25mm

.04mm dia.

<3% @ +/- 1mm from focal point

25uS

40kHz

3 levels

00 to 99

Adjustable

Two 7 segment digits

Two 7 segment digits

Auto-Detect NPN/PN

NO/NC selectable

LOCK / UN-LOCK keypad

Green LED

Red LED

Yellow LED

EEPROM non—volatile memory

51mm (2.0") x 61mm (2.4") x 25mm (1.0")

95 g (0.21 lbs.)

10-24 VDC

60 mA

Discrete output

Supply voltage

-20°C...55°C

-20°C...70°C

Metal alloy

IP67 NOT FOR PRESSURE WASHDOWN

Indicators

7-Segment display

Green LED

Red LED

Yellow LED

LED
 Power
 Detect
 Program

Connector M12

Pin 1

Pin 2

Pin 3

Pin 4

Pin 5

Power to 24VDC
 Discrete output
 PNP/NPN NO/NC
 Ground
 Not used
 Remote LOCK/
 UNLOCK input

WARRANTY EMX INC. the product described herein for a period of 2 years under normal use and service from the date of manufacture. The product will be free from defects in material and workmanship. This warranty does not cover ordinary wear and tear, abuse, misuse, overloading, altered products, or damage caused by the purchaser from incorrect connections, or lightning damage. There is no warranty of merchantability. There are no warranties expressed, implied or any affirmation of fact or representation which extend beyond the description set forth herein. EMX Inc. sole responsibility and liability, and purchaser's exclusive remedy shall be limited to the repair or replacement at EMX's option of a part or parts not so conforming to the warranty. In no event shall EMX Inc. be liable for damages of any nature, including incidental or consequential damages, including but, not limited to any damages resulting from non-conformity defect in material or workmanship.

NOT INTENDED FOR USE IN
PERSONAL SAFETY APPLICATIONS.

MADE IN THE USA

©EMX Industries, Inc. all rights reserved. REV 2.1 8/12/10